

2010

**IKL333 - REBATED
LOUVRE**



IKL - 333

PRODUCT DESCRIPTION

- EXTRUDED ALUMINIUM SECTION (GRADE 6063-T6)
- PITCH 33.5MM
- STANDARD FINISHES:
 - STANDARD RAL OR BS COLOURS
 - SILVER ANODISED (SAA-25)
- DEPTH TO FIT : 36.20 MM
- STANDARD FLYSCREEN: 2 X 2 MM
ON REQUEST: STAINLESS STEEL
FLYSCREEN: 6/6 MM
- PHYSICAL FREE AREA : 33 %
- MAXIMUM FREE AREA : 55 %

SIZES IKL 331

- ALL SIZES ARE POSSIBLE
- WHEN ORDERING :
 - PLEASE QUOTE OPENING WIDTH X HEIGHT

OPTIONS

- DRAINAGE CHANNEL
- BIRD / VERMIN MESH
- SHAPES & CONTINUOUS
- BLANKING PANELS (INSULATION OPTIONS)

FIXING

- WITH BRACKETS OR SPRING CLIPS
- USE OF GLAZING BLOCKS IS RECOMMENDED

TESTED BY BSRIA

- EN 13030:2002



UNIT 1, YARDLEY BROOK
INDUSTRIAL PARK, LEAFORD
WAY, SHARD END,
BIRMINGHAM, B33 9TX

EMAIL:
INFO@IKONALUMINIUM.CO.UK

SALES:
MIKEL@IKONALUMINIUM.CO.UK
UK

WEB:
WWW.IKONALUMINIUM.COM

IKON
ALUMINIUM SYSTEMS

IKL - 333
IKON REBATE
LOUVRE

