



2010

IKL753 - RECESSED  
LOUVRE



# IKL-753

## PRODUCT DESCRIPTION

- EXTRUDED ALUMINIUM SECTION (GRADE 6063-T6)
- PITCH 75MM
- STANDARD FINISHES:
  - STANDARD RAL OR BS COLOURS
  - SILVER ANODISED (SAA-25)
- DEPTH TO FIT : 80.86MM
- STANDARD FLYSCREEN: 2 X 2 MM  
ON REQUEST: STAINLESS STEEL  
FLYSCREEN: 6/6 MM
- PHYSICAL FREE AREA : 55 %
- MAXIMUM FREE AREA : 86 %

## SIZES IKL 753

- MOST SIZES ARE POSSIBLE
  - (MIN . HEIGHT 200MM)
- WHEN ORDERING :
  - PLEASE QUOTE OPENING WIDTH X HEIGHT

## OPTIONS

- DRAINAGE CHANNEL
- BIRD / VERMIN MESH
- SHAPES & CONTINUOUS
- BLANKING PANELS ( INSULATION OPTIONS )

## FIXING

- WITH BRACKETS OR SPRING CLIPS
- USE OF GLAZING BLOCKS IS RECOMMENDED

## TESTED BY BSRIA

- EN 13030:2002



UNIT 1, YARDLEY BROOK  
INDUSTRIAL PARK, LEAFORD  
WAY, SHARD END,  
BIRMINGHAM, B33 9TX

EMAIL:  
[INFO@IKONALUMINIUM.CO.UK](mailto:INFO@IKONALUMINIUM.CO.UK)

SALES:

[MIKEL@IKONALUMINIUM.CO.UK](mailto:MIKEL@IKONALUMINIUM.CO.UK)

WEB:  
[WWW.IKONALUMINIUM.COM](http://WWW.IKONALUMINIUM.COM)

